



SOLiVi4 2.5



2500 Watt solar inverter

Delta, with over 70 years of power electronics experience, presents high efficiency solar inverters designed in Germany. SOLIVIA stands for "SOLar Inverters for Versatile and Intelligent Applications". The 3rd generation of our solar inverters offers cutting-edge and outstanding SOLIVIA features with output power from 2.5 kW to 5.0 kW.

Efficiency & temperature

The brand new SOLIVIA inverters for Australian market have a maximum efficiency of 96%, do not have fans, are dust tight (IP65), and operate over a wide range of temperatures.



Versatile applications

The SOLIVIA string inverters can be used with all common photovoltaic module types, even with back-contact and thin-film modules that

require positive or negative DC grounding. With the optional grounding kit from Delta, the SOLIVIA inverters are a perfect fit for these applications.

INPUT (DC)	
Max. recommended PV power	3100 W
Nominal power	2750 W
Voltage range	125 540 V
MPP range	150 450 V
Full power MPP range	150 450 V
Nominal current	9.8 A
Max. current	18.0 A
Stand-by power	< 0.2 W
OUTPUT (AC)	

OUTPUT (AC) Max. power 2640 W Nominal power 2500 W Voltage range 210 264 V Nominal current 10.9 A Max. current 11.9 A Nominal frequency 50 Hz Frequency range 48.0 52.0 Hz Power factor (cos φ) > 0.99 @ nominal power Total harmonic distortion (THD) < 5 % @ nominal power	Startu-by power	< 0.2 VV
Nominal power 2500 W Voltage range 210 264 V Nominal current 10.9 A Max. current 11.9 A Nominal frequency 50 Hz Frequency range 48.0 52.0 Hz Power factor (cos φ) > 0.99 @ nominal power	OUTPUT (AC)	
Voltage range 210 264 V Nominal current 10.9 A Max. current 11.9 A Nominal frequency 50 Hz Frequency range 48.0 52.0 Hz Power factor (cos φ) > 0.99 @ nominal power	Max. power	2640 W
Nominal current 10.9 A Max. current 11.9 A Nominal frequency 50 Hz Frequency range 48.0 52.0 Hz Power factor (cos φ) > 0.99 @ nominal power	Nominal power	2500 W
Max. current 11.9 A Nominal frequency 50 Hz Frequency range 48.0 52.0 Hz Power factor (cos φ) > 0.99 @ nominal power	Voltage range	210 264 V
Nominal frequency 50 Hz Frequency range 48.0 52.0 Hz Power factor (cos φ) > 0.99 @ nominal power	Nominal current	10.9 A
Frequency range	Max. current	11.9 A
Power factor (cos φ) > 0.99 @ nominal power	Nominal frequency	50 Hz
	Frequency range	48.0 52.0 Hz
Total harmonic distortion (THD) < 5 % @ nominal power	Power factor (cos φ)	> 0.99 @ nominal power
	Total harmonic distortion (THD)	< 5 % @ nominal power

GENERAL SPECIFICATION	
Model name	SOLIVIA 2.5 AP G3
Max. efficiency	96.0 %
Efficiency EU	94.8 %
Operating temperature	-25 +70 °C
Storage temperature	-25 +80 °C
Humidity	0 98 %

STANDARDS	
Protection degree	IP65
Safety class	1
Configurable trip parameters	Yes
Insulation monitoring	Yes
Anti-islanding protection	AS 4777.2;
	AS 4777.3;
	IEC 60255.5

MECHANICAL DESIGN	
Size (L x W x D)	410 x 410 x 180 mm
Weight	21.5 kg
Cooling	Free convection
AC connector	Wieland RST25i3S
DC connector	4 pairs of Multicontact MC4
Communication	2 Harting RJ45 / RS485
Display	LCD; 3 LEDs

DIRECTIVES	
EMC	AS 4777.1; AS 4777.2;
	AS 4777.3; EN 61000-6-2;
	IEC / EN 61000-6-3
Safety	AS/NZS 60950; AS/NZS 3100;
	AS 4777.2; AS 4777.3

Delta Energy Systems (Australia) Pty. Ltd.

Suite 13, Level 4, 150 Albert Road, South Melbourne, VIC 3205, Australia General inquiry: +61 3 8414 8293 Technical support: +61 3 8414 8295 Email: sales.australia@solar-inverter.com



